



Dyna-Blue® Heavy Duty Cable Lubricant

DESCRIPTION

Dyna-Blue® Cable Pulling Lubricant is a clean, slow-drying, easy-to-apply gel lubricant. It has “clingability” for easy handling and hand application. Dyna-Blue is a good lubricant for everyday use in general electrical and communication applications.

Dyna-Blue Lubricant is popular for commercial and institutional pulling because it is non-staining and easy to clean up in these environments.

Dyna-Blue Cable Pulling Lubricant is slow drying. It effectively reduces friction and continues to lubricate for the full length of the pull. Its dried residue is non-conductive and non-combustible.


Dyna-Blue Cable Pulling Lubricant is harmless to humans, environmentally safe, compatible with cable jacket materials and easy to handle.

FRICITION TESTING

Lubricity: Dyna-Blue shows good friction reduction across a broad class of jacket types. Typical values at 200 lbs/ft (2.91 kN/m) normal pressure are shown. Test results are based on the method described in the white paper, “Coefficient of Friction Measurement on Polywater’s Friction Table, 2007” (polywater.com/FTable.pdf). Values are compiled from testing on multiple cable jacket and conduit materials.

| CABLE JACKET | CONDUIT TYPE | | |
|--------------|--------------|-----|-------|
| | EMT | PVC | STEEL |
| XLPE | .18 | .08 | .18 |
| LLDPE | .14 | .11 | .17 |
| PVC | .11 | .11 | .19 |
| CPE | .23 | .21 | .24 |
| THHN | .23 | .09 | .21 |

Coefficient of friction data on additional or specific cable jackets or conduits can be obtained from American Polywater Corporation.



Dyna-Blue Lubricant clings without dripping

PRODUCT FEATURES

- **Clean:** Non-staining gel lubricant.
- **Easy:** Can be applied by hand.
- **High Cling Factor:** Stays on wires during application.
- **Temperature Stable:** No ruined lubricant from freeze/thaw exposure.
- **Wipes Clean and Dry:** Wire markers stick to cable jackets.

END USE

Use for all types of cable installations, including:

- General electrical or communication use
- Overhead and vertical installations
- Indoor or building construction

APPROVALS

UL Listed

UL Listed to Canadian safety standards

CABLE COMPATIBILITY

Tensile and Elongation Effects:

XLPE, LLDPE, VLDPE, PVC, CPE, and CSPE cable jacket materials aged in Dyna-Blue Lubricant per IEEE Standard 1210¹ meet the tensile and elongation retention requirements of that standard.

Polyethylene Stress Cracking:

Dyna-Blue Lubricant shows no stress cracking on LLDPE, MDPE, or HDPE cable jacket when tested per IEEE Standard 1210¹.

Volume Resistivity:

There are no significant changes in the conductive properties of XLPE and EPR semi-conducting compounds when volume resistivity is tested according to IEEE Standard 1210¹.

Building Wire Testing:

THHN and XLPE building wire meet UL tensile, elongation, and voltage withstand requirements after exposure to Dyna-Blue Lubricant as tested by UL requirements².

Cable Approvals:

Dyna-Blue Lubricant is approved by most cable manufacturers. Contact American Polywater for further information.

¹ IEEE Std 1210-2004; IEEE Standard Tests for Determining Compatibility of Cable-Pulling Lubricants with Wire and Cable.

² UL Subject 267, Investigation for Wire-Pulling Compounds.

PHYSICAL PROPERTIES

| PROPERTY | RESULT |
|----------------------------------|-----------------------------|
| Appearance | Thick, light blue gel |
| Wax, Grease and Silicone Content | None |
| Non-Volatile Solids (%) | 3.0% |
| VOC Content | 0 g/L |
| Viscosity | 70,000 – 110,000 cps @10rpm |
| pH | 6.5 – 8.5 |

PERFORMANCE PROPERTIES

Cling Factor:

Cling factor is a measure of the ability to apply the lubricant and have it stay on the jacket while the cable enters the conduit.

A six-inch length (152 mm) of a one-inch (25 mm) diameter cable will hold at least 75 grams of Dyna-Blue Lubricant for one minute when held vertically at 70°F (21°C).

Coatability:

Coatability is a measure of the lubricant's ability to coat the jacket as a thin film for continued lubricity on longer pulls.

Dyna-Blue Lubricant will wet out evenly on cable jacket surfaces. It will not bead up or rub off of the jacket sample. A one-inch (25 mm) diameter XLPE cable dipped six inches (152 mm) into the Dyna-Blue, then withdrawn and held vertically, will retain at least 25 grams of Dyna-Blue Lubricant for one minute at 70°F (21°C).

Combustibility:

Lubricant has no flash point and dried residue is non-flammable.

APPLICATION PROPERTIES

Application Systems:

Dyna-Blue Lubricant has a thick gel consistency that makes it easy to hand apply.

Dyna-Blue Lubricant can also be pumped directly into the conduit or onto the cable using the Polywater LP-D5 specialty lubricant pumps. Pumps allow hands-free transfer and consistent application of lubricant. However, the thick gel consistency limits the length of the discharge hose and the pumping rate. The LP-D5 supports Dyna-Blue Lubricant application rates of 1 to 2 gallon (4 to 8 liters) per minute.

Pull-Planner™ Tension Calculation Software is available from Polywater. Pulling tension estimations can ensure the use of appropriate pulling equipment and that the cable is installed within safe limits.

Temperature Use Range:

20°F to 120°F (-5°C to 50°C).

Temperature Stability:

No phase-out after five freeze/thaw cycles or 5-day exposure at 120°F (50°C).

Cleanup:

Dyna-Blue Lubricant is non-staining. Complete cleanup is possible with water.

Storage and Shelf Life:

Store Dyna-Blue Lubricant in a tightly sealed container away from direct sunlight. Lubricant shelf life is two years.

DIRECTIONS FOR USE

Dyna-Blue Lubricant can be squeezed, pumped or hand applied directly onto the wire or cable. The thick clingy gel character allows Dyna-Blue to be applied to vertical installations. Conduit should be clean and continuous.

To prelubricate for long or difficult pulls, squirt a liberal amount of Dyna-Blue Lubricant into the conduit before the pull begins and use a mandrel or a swab on the winch line to spread the lubricant during the pull.

Clean-up by wiping off any excess lubricant with a rag.

Recommended Lubricant Quantity:

$$Q = k \times L \times D$$

Where:

Q = quantity in gallons (liters)

L = length of conduit in feet (meters)

D = ID of the conduit in inches (mm)

k = 0.0015 (0.0008 if metric units)

The quantity that is appropriate for any given pull can vary from this recommendation by 50%, depending on the complexity of the pull. Consider the following factors:

Cable weight and jacket hardness

(*Increase quantity for stiff, heavy cable*)

Conduit type and conditions

(*Increase quantity for old, dirty or rough conduits*)

Conduit fill

(*Increase quantity for high percent conduit fill*)

Number of bends

(*Increase quantity for pulls with several bends*)

Pulling environment

(*Increase quantity for high temperatures*)

MODEL SPECIFICATION

The statement below may be inserted into a customer specification to help maintain engineering standards and ensure work integrity.

The cable pulling lubricant shall be Dyna-Blue® Lubricant. The cable pulling lubricant shall produce a low coefficient of friction on a wide variety of cable jacket materials. The lubricant shall be UL listed. It shall be easy to handle and adhere well to the cable.

The lubricant shall pass the IEEE 1210, Standard Tests for Determining Compatibility of Cable-Pulling Lubricants with Wire and Cable. It shall pass physical compatibility tests on LLDPE, XLPE, CPE, and PVC cable jacket or sheath materials. It shall not stress crack polyethylene per ASTM Standard 1693. There shall be no significant changes in the conductive properties of XLPE and EPR semi-conducting compounds when the lubricant's effect on volume resistivity is tested according to IEEE Standard 1210.

ORDER INFORMATION

| CAT # | PACKAGE DESCRIPTION |
|--------|--|
| D-35 | 1-qt. squeeze bottle (0.95 liter) 12/case |
| D-128 | 1-gal. pail (3.78 liter) 4/case |
| D-640 | 5-gal. pail (18.9 liter) |
| D-Drum | 55-gal. drum (208 liter) |

CONTACT US

1-800-328-9384 Toll Free | 1-651-430-2270 Main | 1-651-430-3634 Fax | email: support@polywater.com

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from product's use, regardless of the legal theory asserted.

